

Declaration of performances (regulation (EU) Nr. 305/2011)

DoP 104

| 1 | Hamberger Laminate Flooring | | | | | | | EN 13329 : 2009 |
|---|---|-------------------------|---------------|---------------|----------------|-----------------|-----------------------|---|
| 2 | Floor covering for internal use under dry conditions | | | | | | | |
| 3 | Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim | | | | | | | |
| 4 | System of assessment and verification of constancy of performance | | | | | | | 3 ^{*)} |
| 5 | Thickness | 7 mm | 8 mm | 10 mm | PS +2 mm | Silent +2 mm | Silent CT +2 mm | |
| | Key properties | | | | | | | |
| | Reaction to fire*) | C _{FI} - s1 | | | | | | EN 14041: 2004 +AC:2005 +AC:2006 |
| | PCP concentration | ≤ 5 x 10 ⁻⁶ⁿ | | | | | | |
| | Emission of formaldehyde ^{*)} | E1 | | | | | | |
| | Water resistance | NPD | | | | | | |
| | Slip resistance | DS | | | | | | |
| | Electrical behaviour | < 2kV | | | | | | |
| | Thermal conductivity | 0,121 W/mK | 0,123 W/mK | 0,132 W/mK | +0,035 W/mK | +0,200 W/mK | +0,050 W/mK | |
| | Durability as regards reaction to fire | NPD | | | | | | |

The performance of the product identified in (1) is in conformity with the declared performance in (5). This declaration of performance is issued under the sole responsibility of the manufacturer (3).

Signed for and on behalf of the manufacturer:

Peter Huber, head of production

Stephanskirchen, 17.02.2016

[&]quot;) In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 2097 eco-Institut, NB 0766 eph Dresden, NB 0672 MPA Stuttgart) has/have performed type testing according to the system specified in (4).