




13

Declaration of performances
(regulation (EU) Nr. 305/2011)

DoP 113

1	Hamberger multi layer parquet, 3-layer-parquet				EN 13489: 2003	
2	Floor covering for internal use under dry conditions					
3	Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim					
4	System of assessment and verification of constancy of performance				3 ^{*)}	
5	Thickness	11 mm (HDF)	12 mm	12mm (HDF)	13,5 mm	EN 14342: 2013
	Mass density	> 500 kg/m ³				
	Key properties					
	Reaction to fire ^{*)}	D _{FI} - s1				
	Emission of formaldehyde ^{*)}	E1				
	Content of PCP	≤ 5x10 ⁻⁶ⁿ				
	Emission of other dangerous substances	NPD				
	Breaking strength	NPD				
	Slip resistance	NPD				
	Thermal conductivity	0,145 W/mK	0,122 W/mK	0,171 W/mK	0,123 W/mK	
Natural durability	1 (DIN EN 350-1:1994)					
6	<p>The performance of the product identified in (1) is in conformity with the declared performance in (5). This declaration of performance is issued under the sole responsibility of the manufacturer (3).</p> <p>Signed for and on behalf of the manufacturer</p> <p><i>Peter Huber,</i> <i>head of production</i></p> <p><i>Stephanskirchen, 17.02.2016</i></p> 					
<p>^{*)} In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 0765 WKI Braunschweig, NB 0766 eph Dresden) has/have performed type testing according to the system specified in (4).</p>						