

CARE AND MAINTENANCE

UV OIL

Room Conditions

Timber likes pleasant room conditions similar to humans; a room temperature of 20°C and humidity of about 50%. A humidity controller may be required. All rooms, which have timber flooring, should ideally be maintained at the above.

UV OIL

A UV oiled finish means that the oil is cured under ultra violet lights. This allows more oil to be used and results in a more durable finish than natural oil. As with all floor finishes eventually the surface will wear down and require refinishing. To prolong the lifespan of the floor it is important to use the recommended maintenance products below as it provides ongoing protection to the floor surface.

Higher traffic / heavier use areas will require more frequent use of the Natural Soap and a shorter period of time in between coats of maintenance gel. The floor should be reviewed regularly and maintained for signs of excessive wear and appropriate action should be taken to avoid deterioration of the finish. If there are other building works taking place after installation the floor should be covered to protect the finish. Please see the reverse of each Woca product for full usage instructions. There are also detailed video instructions available at www.wocadenmark.com/video

CLEAN (REGULARLY)



Natural Soap

Avg. Coverage: 320-400m²/L

Should be used for cleaning all wood floors with UV Oil and DSC finishes. Woca Natural Soap contains high quality vegetable oils that help prevent the wood from drying out. Available in the following: Natural (beige and dark tone wood floors), White (light tone wood floors).

REJUVENATE (AS REQUIRED)



Intensive wood cleaner

Avg. Coverage: 200-300m²/L

This is strictly for preparing wooden floors for further treatment. Intensive wood cleaner is efficient at removing stains caused by dirt or grease whilst also helping to open the wood to receive further oil treatments.

Heavy Wear

Areas with heavy wear can be repaired with Maintenance Gel after cleaning. Particularly strong stains may be removed with Woca Spot Remover.



Maintenance Gel

Avg. Coverage: 20-30m²/L

This is ideal for refreshing oiled wood floors, particularly UV oiled floors & DSC Finish. Can be applied manually with a polish pad. Renew and rejuvenate with maintenance gel once a year or as required depending on wear/use.

Protecting your floor

To preserve quality and beauty of your floor the following guidelines should be followed.

- Use protective pads and castor cups under chairs and furniture legs. Use good quality polycarbonate mats under wheeled office chairs.
- We recommend that good quality entrance barrier mats are used at all external entrances to the hardwood flooring to collect grit and moisture from the underside of footwear.
- Never use a rubber mat, with Styrofoam or plastic backing.
- For moving heavy furniture place a piece of carpet face down between the legs and the flooring and pull on the carpet to move the furniture.
- We would advise that during installation / other building works that the timber floor is covered with a heavy duty breathable floor protection roll / sheets to protect the finish.
- Do not apply adhesive / decorators tape directly to the floor finish.