


ADJUSTABLE PEDESTAL AK 3.5/5

TECHNICAL
DATASHEET

SPECIFICATIONS

Consists of 2 pieces and is placed on the walls of a terrace. The bottom piece has 8 vertical reinforcement ribs. The top piece has 8 recesses to be able to block the upper plate.

Color	Black
Support area	300 cm ²
Outside diameter	164/215 mm
Weight	140 g/piece
Adjustable height	35 - 50 mm



Recycled material



Weatherproof



Resistant to temperatures between
-25 and +70°C



PP compound



Compliant with the DTU standard 43.1
and 51.4




Capacity: 2.400 kg/m²



Tested on Broof T4 and BFL-S1

OTHER PEDESTALS WALL VERSION




AK 5/8


OTHER PEDESTALS




PV 3.5/5




PV 11/14



PV 5/8



PV 14/17



PV 8/11

SUPPORT PLATES

For tiles



C2/4T

For wood




CPV+



C3/4T

Other



C0



C6/4T



STICKSOL

ACCESSORIES

Extension piece



F30



AF100

Slope corrector



HA5

Fitting pieces



1 - 3 mm

PACKAGING

Bag

Dimensions	1.450 x 750 mm
Gross weight	7 kg
Quantity	50 pieces/bag

Pallet

Dimensions	1.200 x 1.100 x 2.000 mm
Gross weight	166 kg
Quantity	24 pieces/bag - 1.200 pieces



Made in Belgium



ADJUSTABLE PEDESTAL AK 3.5/5

TECHNICAL
DATASHEET

LOAD/M²

Every 600 mm l/w	1.350 kg/m ²
Every 500 mm l/w	2.400 kg/m ²
Every 400 mm l/w	3.750 kg/m ²

Tiles

600 x 600 mm (2,25 pcs/m ²)	1.350 kg/m ²
500 x 500 mm (4,00 pcs/m ²)	2.400 kg/m ²
400 x 400 mm (6,25 pcs/m ²)	3.750 kg/m ²

TEST DE COMPRESSION (ZWICK)

1.440 kg

