


ADJUSTABLE PEDESTAL PV 8/11

TECHNICAL DATASHEET

SPECIFICATIONS

Consists of 2 pieces. The bottom piece has 8 vertical reinforcement ribs. The top piece has 8 recesses to be able to block the upper plate.

Color	Black
Support area	300 cm ²
Outside diameter	215 mm
Weight	246 g/piece
Adjustable height	80-110 mm



Recycled material

Weatherproof

Resistant to temperatures between -25 and +70°C


PP compound

Compliant with the DTU standard 43.1 and 51.4


Capacity: 2.400 kg/m²

Tested on Broof T4 and BFL-S1

OTHER PEDESTALS



PEDESTALS WALL VERSION



TOP PLATES

For tiles




C2/4T



C3/4T



C6/4T



STICKSOL

For wood



CPV+

Other



CO

ACCESSORIES

Extension piece



F30



AF100

Slope corrector



HS2



HA5

Fitting pieces



1 - 3 mm

PACKAGING

Bag

Dimensions	1.450 x 750 mm
Gross weight	13 kg
Quantity	50 pieces/bag

Pallet

Dimensions	1.200 x 1.100 x 2.000 mm
Gross weight	192 kg
Quantity	14 pieces/bag – 700 pieces



ADJUSTABLE PEDESTAL PV 8/11

TECHNICAL
DATASHEET

LOAD/M²

Wood

Every 600 mm l/w	1.350 kg/m ²
Every 500 mm l/w	2.400 kg/m ²
Every 400 mm l/w	3.750 kg/m ²

Tiles

600 x 600 mm (2,25 pcs/m ²)	1.350 kg/m ²
500 x 500 mm (4,00 pcs/m ²)	2.400 kg/m ²
400 x 400 mm (6,25 pcs/m ²)	3.750 kg/m ²

PRESSURE TEST (ZWICK)

1.630 kg

