

	QUALITÄTSMANAGEMENT HANDBUCH	
Qualitätsmanagementsystem technical datasheet		

12mm Robusto 4V

1. Product description

- | | |
|----------------------------|---|
| 1.1. Format | 1375 x 188 x 12 mm |
| 1.2. Packing | 5 boards each pack = 1,293 m ² |
| 1.3. Technical description | |
| - Surface | Three-dimensional interlaced melamine resin |
| - Decor | Melamine resin impregnated printed paper |
| - Core layer | HDF High Density Fiberboard |
| - Balance film | Melamine resin impregnated paper |
| 1.4. Installation | Mechanical looking system , Clic-System – much easier to install , up to 50% quicker to install (against other clic systems). Floating installation according to the installation description . |
| 1.5. Classification | ISO 10874 class 23 : heavy domestic use
class 33 : heavy commercial use |
| | EN 14041 CE – Mark |
| 1.6. Fire classification | EN 13501 C _{fl} – s1 (Hardly inflammable ~ B1) |
| 1.7. Emission | E1 lower than 0,05 ppm |
| 1.8. Slip resistance | Technical class DS |
| 1.9. Thermal conductivity | Thermal resistance according to DIN EN 12667 R= 0,0885 [(m ² * K)/W] |

